

Product Code . EL-RAACLE-11503

Capacity Control Methods in Refrigeration



Description




Capacity Control Methods in Refrigeration

The compressor drive motor is controlled using a frequency converter. In the first compartment the temperature is regulated using an intake pressure controller and thermostat (mechanical regulation), in the second compartment using a case controller (electronic regulation). The evaporators are in individual insulated compartments. The cooling capacity of the system with 2 separate evaporators can be changed by adjusting the speed of the open compressor. In both cooling compartments a cooling load can be generated using an electrical heater. Fans ensure even temperature distribution. The signals provided by these sensors are also used by the case controller. The system is equipped with temperature sensors at all relevant measuring points. A bypass capacity regulator is installed in the refrigerant circuit that connects the high and low pressure sides of the compressor.

We are leading manufacturers, suppliers of Capacity Control Methods in Refrigeration for Refrigeration and Air Conditioning Lab Equipments. Contact us to get high quality Capacity Control Methods in Refrigeration for Refrigeration and Air Conditioning Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.

```
{ "@context": "https://schema.org/", "@type": "Product", "name": "Capacity Control Methods in Refrigeration", "image": "http://www.educational-equipments.com/images/catalog/product/322187869CapacityControlMethodsInRefrigeration.jpg", "description": "Capacity Control Methods in Refrigeration The compressor drive motor is controlled using a frequency converter. In the first compartment the temperature is regulated using an intake pressure controller and thermostat (mechanical regulation), in the second compartment using a case controller (electronic regulation). The evaporators are in individual insulated compartments. The cooling capacity of the system with 2 separate evaporators can be changed by adjusting the speed of the open compressor. In both cooling compartments a cooling load can be generated using an
```

electrical heater. Fans ensure even temperature distribution. The signals provided by these sensors are also used by the case controller. The system is equipped with temperature sensors at all relevant measuring points. A bypass capacity regulator is installed in the refrigerant circuit that connects the high and low pressure sides of the compressor. We are leading manufacturers, suppliers of Capacity Control Methods in Refrigeration for Refrigeration and Air Conditioning Lab Equipments. Contact us to get high quality Capacity Control Methods in Refrigeration for Refrigeration and Air Conditioning Lab Equipments for schools, colleges, universities, research labs, laboratories and various industries.", "brand": "Educational equipment", "sku": "5", "gtin8": "5", "gtin14": "5", "gtin13": "5", "mpn": "5", "aggregateRating": { "@type": "AggregateRating", "ratingValue": "5", "bestRating": "5", "worstRating": "0", "ratingCount": "15" } }

Educational Lab Equipments,
#449, HSIIDC, Industrial Area, Saha, Haryana
Direct Contact Details  +91-98173-19615  sales@educational-equipments.com
 www.educational-equipments.com